TABLE OF CONTENTS

| Section | <u>Page</u> |
|--|-------------|
| 1. INTRODUCTION | 1—1 |
| 2. PROCESS DESCRIPTION | 2—1 |
| 2.1 SUMMARY OF PERMITTING HISTORY | 2—1 |
| 2.1.1 CT-234A, CT-234A2, and OP-154 | 2—3 |
| 2.1.2 CT-643A, and OP-181 | 2—4 |
| 2.1.3 MD-117 and OP-257 | 2—5 |
| 2.1.4 MD-132 and OP-258 | 2—6 |
| 2.1.5 CT-946 | 2—6 |
| 2.1.6 MD-229 | 2—8 |
| 2.1.7 MD-282 | 2—9 |
| 2.2 EXISTING FACILITY | 2—9 |
| 2.2.1 Existing Soda Ash Production Plant | 2—9 |
| 2.2.2 Alkaten® Production Plant | 2—11 |
| 2.2.3 Caustic/Sulfite Plant. | 2—11 |
| 2.2.4 Bagging Facility | 2—12 |
| 2.3 SODA ASH EXPANSION | 2—12 |
| 2.4 SODA ASH EXPANSION CONSTRUCTION AND OPERATION SCHEDULE | 2—13 |
| 2.5 REGULATORY REQUIREMENTS | 2—14 |
| 3. EMISSIONS INVENTORY | 3—1 |
| 3.1 EXISTING FACILITY WITH PROPOSED MODIFICATIONS | 3—2 |
| 3.1.1 Air Toxics Emissions | 3—2 |
| 3.1.2 Basis of Source Emissions Estimates | 3—8 |
| 3.2 BACKGROUND SOURCES | 3—21 |
| 3.3 NEW SOURCE PERFORMANCE STANDARD APPLICABILITY | 3—22 |
| 3.4 ASSESSMENT OF BEST AVAILABLE CONTROL TECHNOLOGY (BACT) | 3—23 |
| 3.4.1 Particulate Matter | 3—24 |

| Section | <u>Page</u> |
|---|-------------|
| 3.4.2 Nitrogen Oxides (NO _X) | 3—29 |
| 3.4.3 Volatile Organic Compounds (VOCs) including Hazardous Air Pollutants (HAPs) | 3—33 |
| 3.4.4 Carbon Monoxide (CO). | 3—45 |
| 3.4.5 Other Pollutants | 3—47 |
| 4. EXISTING ENVIRONMENT | 4—1 |
| 4.1 TOPOGRAPHY | 4—1 |
| 4.2 AIR QUALITY | 4—1 |
| 4.3 CLIMATE AND SITE METEOROLOGY | 4—4 |
| 4.4 SOILS AND VEGETATION | 4—6 |
| 5. IMPACT ASSESSMENT APPROACH | 5—1 |
| 5.1 AIR QUALITY MODELING | |
| 5.1.1 Criteria Pollutant Analysis | |
| 5.1.2 HAPs Analysis | 5—8 |
| 5.2 METEOROLOGICAL DATA | 5—11 |
| 5.3 SOURCE CHARACTERISTICS | 5—11 |
| 5.3.1 Stack Parameters | 5—11 |
| 5.3.2 Good Engineering Practice Stack Height Analysis | 5—16 |
| 5.4 RECEPTOR SELECTION | 5—20 |
| 5.5 AIR QUALITY RELATED VALUES | 5—20 |
| 5.5.1 Plume Visibility | 5—20 |
| 5.5.2 Regional Haze | 5—21 |
| 5.5.3 Acid Deposition | 5—21 |
| 6. RESULTS | 6—1 |
| 6.1 IMPACTS DUE TO EXPANSION | 6—1 |
| 6.2 AAOS COMPLIANCE ASSESSMENT | 6—4 |

TABLE OF CONTENTS

| Section | <u>Page</u> |
|----------------------------|-------------|
| 6.3 PSD INCREMENT ANALYSIS | 6—6 |
| 6.4 HAPS | 6—7 |
| 6.5 PLUME VISIBILITY | 6—10 |
| 6.6 REGIONAL HAZE | 6—11 |
| 6.7 ACID DEPOSITION | 6_11 |

| Section | <u>Page</u> |
|--|-------------|
| TABLE 2-1: SUMMARY OF PERMIT HISTORY | 2—1 |
| TABLE 2-2: MD-229 PSD EMISSIONS | 2—8 |
| TABLE 2-3: MD-282 PSD EMISSIONS AND NETTING | 2—9 |
| TABLE 2-4: SIGNIFICANT EMISSION RATES | 2—15 |
| TABLE 3-1: PSD NET EMISSIONS CHANGES | 3—2 |
| TABLE 3-2: EPA METHOD 0010 SEMI-VOLATILE ORGANIC HAPS | 3—5 |
| TABLE 3-3: EPA METHOD 0011 ALDEHYDES AND KETONES | 3—6 |
| TABLE 3-4: EPA METHOD 18 HAPS | 3—7 |
| TABLE 3-5: MINE VENT EXHAUST HAP EMISSIONS | 3—8 |
| TABLE 3-6: BASIS OF EMISSION RATES FOR EXPANSION SOURCES | 3—9 |
| TABLE 3-7: BASIS OF EMISSION RATES FOR MODIFIED SOURCES | 3—10 |
| TABLE 3-8: AQD #80 CO EMISSIONS | 3—13 |
| TABLE 3-9: AQD #80 VOC EMISSIONS | 3—13 |
| TABLE 3-10: AP-42 EMISSION FACTORS FOR AQD #82 | 3—15 |
| TABLE 3-11: AP-42 EMISSION FACTORS FOR AQD #85 | 3—16 |
| TABLE 3-12: MODIFIED EXISTING PARTICULATE EMISSION LIMITS | 3—19 |
| TABLE 3-13: EMISSION RATES OF ALL SOURCES | 3—20 |
| TABLE 3-15: COST EFFECTIVENESS OF FLARE | 3—37 |
| TABLE 4-1: MAXIMUM MEASURED POLLUTANT CONCENTRATIONS | 4—2 |
| TABLE 4-2: NATIONAL AND WYOMING AMBIENT AIR QUALITY STANDARDS | 4—3 |
| TABLE 4-3: AVERAGE PRECIPITATION - GREEN RIVER, WYOMING | 4—5 |
| TABLE 4-4: AVERAGE TEMPERATURE FOR THE ROCK SPRINGS. WYOMING AIRPORT | ·4—6 |
| TABLE 5-1: AIR QUALITY MODELING CRITERIA | 5—4 |
| TABLE 5-2: PM ₁₀ BACKGROUND MONITORED DATA | 5—7 |
| TABLE 5-3: NATICH LOWEST ALLOWABLE AMBIENT HAP LEVELS | 5—9 |
| TABLE 5-4: NATICH HIGHEST ALLOWABLE AMBIENT HAP LEVELS | 5—10 |
| TABLE 5-5: STACK PARAMETERS | 5—12 |
| TABLE 5-6: EMISSION RATES (POUNDS PER HOUR) | 5—14 |
| TABLE 5-7: PRELIMINARY GEP ANALYSIS | 5—18 |
| TABLE 5-8: LAKES CONSIDERED IN ACID DEPOSITION ANALYSIS | 5—22 |
| TABLE 6-1: MAXIMUM IMPACTS FROM EMISSIONS DUE TO EXPANSION | 6—2 |
| TABLE 6-2: NAAQS/WAAQS COMPLIANCE DEMONSTRATION | 6—5 |
| TABLE 6-3: CLASS I PSD INCREMENT ANALYSIS | 6—6 |
| TABLE 6-4: SUMMARY OF HAP MODELING - FIVE YEAR MAXIMUM IMPACT | 6—8 |
| TABLE 6-5: SUMMARY OF HAP MODELING - STATUS | 69 |
| TABLE 6-6: CALCULATED RISK | 6—10 |

TABLE OF TABLES

| Section | <u>Page</u> | |
|---|-------------|------|
| TABLE 6-7: SUMMARY OF MAXIMUM ACID DEPOSITION RESULTS | | 6—13 |

TABLE OF FIGURES

SECTION 2

| Figure 2-1Project Location Map | |
|--|--|
| SECTION 3 | |
| Figure 000-PF-131 Primary Screening & Storage Process Flow Diagram | |
| Figure 000-PF-132A Conveying, Crushing & Storage Process Flow Diagram | |
| Figure 000-PF-133BCalcining Process Flow Diagram | |
| Figure 000-PF-133CCalcining Process Flow Diagram | |
| Figure 000-PF-134 Leaching & Thickening Process Flow Diagram | |
| Figure 000-PF-134A Leaching & Thickening Process Flow Diagram | |
| Figure 000-PF-134B Leaching & Thickening Process Flow Diagram | |
| Figure 000-PF-135 Primary Filtration Process Flow Diagram | |
| Figure 000-PF-135B Primary and Secondary Filtration Process Flow Diagram | |
| Figure 000-PF-136 Secondary Filtration Process Flow Diagram | |
| Figure 000-PF-138B . Mechanical Recompression Crystallizing Process Flow Diagram | |
| Figure 000-PF-138C . Mechanical Recompression Crystallizing Process Flow Diagram | |
| Figure 000-PF-139Weak Liquor and Process Water Tanks Process Flow Diagram | |
| Figure 000-PF-139A Weak Liquor and Process Water Tanks Process Flow Diagram | |
| Figure 000-PF-140B Centrifuge & Purge Recovery Process Flow Diagram | |
| Figure 000-PF-140D Centrifuge & Purge Recovery Process Flow Diagram | |

TABLE OF FIGURES (Continued)

| Product Drying, Sizing & Loadout Process Flow Diagram | Figure 000-PF-141B |
|--|--------------------|
| Product Drying, Sizing & Loadout Process Flow Diagram | Figure 000-PF-141C |
| Product Drying, Sizing & Loadout Process Flow Diagram | Figure 000-PF-141D |
| Fines Recovery Process Flow Diagram | Figure 000-PF-142B |
| | Figure 000-PF-143 |
| Air Quality Sources Plot Plan | Figure AQ-300 |
| | SECTION 6 |
| Dispersion Modeling Result PM ₁₀ - Annual Average | Figure 6-1 |
| Dispersion Modeling Result PM ₁₀ - 24 HR. Average | Figure 6-2 |

TABLE OF ACRONYMS

| μg | micrograms |
|----------|--|
| AALs | Allowable Ambient Levels |
| AAQS | Ambient Air Quality Standards |
| ANC | Acid Neutralizing Capacity |
| AQD | Air Quality Division |
| AQRVs | Air Quality Related Values |
| BACT | Best Available Control Technology |
| BPIP | Building Profile Input Program |
| CAA | Clean Air Act |
| CaO | |
| CFR | Code of Federal Regulations |
| CO | |
| CT | |
| EPA | United States Environmental Protection Agency |
| ESP | Electrostatic Precipitator |
| GEP | Good Engineering Practice |
| gr/dscf | grains per dry standard cubic foot |
| - HAP | Hazardous Air Pollutant |
| HSH | High/Second High |
| ISC3 | Industrial Source Complex Model - Version 3 |
| ISCST3 | Industrial Source Complex Short Term Model - Version 3 |
| | Interagency Workgroup on Air Quality Modeling |
| K | Degrees Kelvin |
| | Lowest Achievable Emission Rates |
| | pounds per million British Thermal Units |
| | |
| | |
| | million tons per year |
| | Sodium Carbonate (Soda Ash) |
| | Sodium Sulfite (Sulfite) |
| – 2 – 3 | |

TABLE OF ACRONYMS

| National Ambient Air Quality Standa | NAAQS |
|--|-----------------|
| National Air Toxics Information Clearinghor | NATICH |
| Sodium Hydroxide (Caustic So | NaOH |
| Nitrogen Oxid | NO _x |
| New Source Performance Stand | NSPS |
| Particulate Matter less than 10 Micromet | PM₁0 |
| pounds per h | PPH |
| Prevention of Significant Deteriorat | PSD |
| Standard Deviat | SD |
| Significant Impact Lev | SILs |
| Solvay Soda Ash Joint Vent | SSAJV |
| Standard Deviat | Std Dev |
| Southwest Wyoming Technical Air For | SWWTAF |
| Urban Airshed Mo | JAM |
| Universal Transect Merid | JTM |
| Volatile Organic Compoui | VOC |
| Wyoming Ambient Air Quality Standa | WAAQS |
| Wyoming Air Quality Standards and Regulation | WAQS&R |
| Wyoming Department of Environmental Qua | WDEQ |

TABLE OF CAS NUMBERS

| Compound | CAS# |
|-------------------------------------|-------------------|
| ACETALDEHYDE | 75-07-0 |
| ACETONE | 67-64-1 |
| ACETOPHENONE | 98-86-2 |
| ACROLEIN | 107-02-8 |
| ACRYLONITRILE | 107-13-1 |
| BENZENE | 71-43-2 |
| BIPHENYL | 92-52-4 |
| BIS(2-ETHYLHEXYL)PHTHALATE | 117-81-7 |
| 1,3 BUTADIENE | 106-99-0 |
| 2-BUTANONE (METHYL ETHYL KETONE) | 78-93-3 |
| 2-CHLOROACETOPHENONE | 532-27-4 |
| CUMENE | 98-82-8 |
| DIBENZOFURAN | 132-64-9 |
| DI-N-BUTYL PHTHALATE | 84-74-2 |
| ETHYL BENZENE | 100-41-4 |
| FORMALDEHYDE | 50-00-0 |
| HEXANE | 110-54-3 |
| METHYLENE CHLORIDE | 75-09-2 |
| 3/4-METHYLPHENOL | 108-39-4/106-44-5 |
| N,N-DIMETHYLANILINE | 121-69-7 |
| NAPHTHALENE | 91-20-3 |
| PHENOL | 108-95-2 |
| PROPIONALDEHYDE | 123-38-6 |
| STYRENE | 100-42-5 |
| TOLUENE | 108-88-3 |
| 1,1,1-TRICHLOROETHANE | 71-55-6 |
| TRICHLOROETHENE (TRICHLOROETHYLENE) | 79-01-6 |
| XYLENE | 1330-20-7 |